

TEFLON PIPE DOPE (TPD)

Pipe Thread Sealant

ACE TEFLON PIPE DOPE (TPD) is a non-toxic, brush in can, soft set, non hardening, smooth, grit-free, white, homogenized teflon pipe joint compound for use on metal and plastic threaded connections (PVC, ABS, CPVC, Nylon, Polypropylene). NSF Certified. Will not transfer any taste or odor to the system being sealed. **ACE TEFLON PIPE DOPE (TPD)** is for use on metal and plastic threaded connections and is formulated for use on all types of systems carrying any liquid or gas. **DO NOT USE ON OXYGEN, FLOURINE and LIQUID SODIUM.** Ideal for food and water systems. Temperatures range for gas and liquids: -50°F (-45°C) to +400°F (+240°C). Pressure range for gases up to 3000 psi, liquids up to 10000psi.

FEATURES & BENEFITS

- Safe on faucet and valve seals - non-toxic and lead free.
- Lubricates as it seals - non-staining and non-seizing.

DIRECTIONS for USE: Stir before use. Clean oil, dirt, grease or any other foreign matter from threads. Apply **ACE TEFLON PIPE DOPE (TPD)** liberally to male threads only. Insert male end into female end and gently apply pressure until full lock is secure. Wipe area with clean cloth.

SAFETY: Do not ingest. For eye contact, flush thoroughly with clean water for at least 15 minutes. Wash hands thoroughly after use.

CAUTION: Wash hands thoroughly after use. **KEEP OUT OF REACH OF CHILDREN.**

PHYSICAL PROPERTIES

APPEARANCE	Paste
COLOR	White
ODOR	None
pH	N/A
FLASH POINT	160°F
SPECIFIC GRAVITY	1.52
PACKAGING	24x1/2 pint cans/case 12x1 pint cans/case

Read Material Safety Data Sheet overleaf.

Atlantic Chemical & Equipment Company
3471 Atlanta Industrial Pkwy - Suite 200 - Atlanta, Ga 30331
Telephone 800 929 2436 Web Address www.atlanticchemical.com